

H.E. Williams, Inc.

# OGP29 Series:

## DECORATIVE LUMINAIRE

### TEARDROP LUMINAIRE WITH FLUTED DECORATIVE HOUSING FROM WILLIAMS OUTDOOR!

Offered with a choice of three different refractor materials, each in two distributions, the OGP29 is extremely versatile. The cast aluminum ballast housing combines a partially fluted dome and tailored details to create an attractive addition to Williams' growing Outdoor line.

- HOUSING – One-piece cast aluminum ballast housing, .188" minimum wall thickness, with exclusive self-leveling twist-lock fitter.
- HOOD – Spun .080" aluminum reflector hood. Underside finish is highly-reflective, non-glare white polyester powder coat.
- REFRACTOR – Teardrop-shaped refractors are available in both Type III and Type V distributions. Choose from acrylic, borosilicate glass, or polycarbonate.
- ELECTRICAL – PSMH: Rated -20°F minimum starting temperature. HPS: Rated -40°F minimum starting temperature. Prewired at factory to a disconnect plug for easy field installation.
- FINISH OPTIONS – Super durable polyester powder coat meets and exceeds AAMA 2604 specifications for outdoor durability.
- MOUNTING – Williams' exclusive self-leveling twist-lock fitter must be mounted to Williams' standard (TL2) twist-lock hub (see Williams' Decorative Pole Top Assemblies).
- LABELS – cCSAus certified as luminaire suitable for wet location.
- This fixture is proudly made in the USA.

OGP29 Series



H.E. Williams, Inc.  
831 W. Fairview Ave.  
Carthage, MO 64836  
Ph: 417-358-4065  
Fax: 417-358-6015

A Visible Difference™