INFORMATION

STANDBY LIGHTING OPTIONS

SHADED AREAS INDICATE AVAILABILITY

BODINE PN	WILLIAMS PN	GENERIC PN	DESCRIPTION	LUMEN RANGE	T4 COMPACT							LONG TWIN TUBE				T8					T5					
					05T4	07T4	09T4	13T4	13T4Q	18T4Q	26T4Q	18TT	40TT	50TT	55TT	17	32	40	59	86	14T5S	21T5S	28T5S	24T5H	39T5H	54T5H
B213	EM213		1 lamp EM (2-pin)	200 - 625	■	■	■	■																			
B30 [1]	EM3/1		1 lamp EM	1450 - 3500								■	■			■	■	■	■	■						
B30 [1]	EM3/2		2 lamp EM	1450 - 3500								■				■	■									
B50 [1, DL]	EM5/1	EM1400/1	1 lamp EM	1100 - 1400								■	■	■		■	■	■	■	■						
B50 [1, DL]	EM5/2	EM1400/2	2 lamp EM	1100 - 1400								■				■	■									
B50RCT [1]	EM5RCT/1		1 lamp EM	1100 - 1400								■	■			■	■	■	■	■						
B50RCT [1]	EM5RCT/2		2 lamp EM	1100 - 1400								■				■	■									
B50ST [1]	EM5ST/1		1 lamp EM	1100 - 1400								■	■	■	■	■	■	■	■	■						
B50ST [1]	EM5ST/2		2 lamp EM	1100 - 1400								■				■	■									
B60 [DL]	EM6/1	EM700	1 lamp EM	600 - 700								■	■			■	■	■	■	■						
B60 [DL]	EM6/2		2 lamp EM	600 - 700												■	■									
B70A [DL, 4]	EM7A	EM700	1 lamp EM	600 - 700								■	■			■	■	■	■	■						
B90 [DL]	EM9	EM500	1 lamp EM	500 - 600								■	■			■	■									
B94C [2, 3, DL]	EM94C/1		1 lamp EM (4-pin)	300 - 750					■	■	■	■														
B94C [2, 3, DL]	EM94C/2		2 lamp EM (4-pin)	300 - 750					■	■	■	■				■										
B100	EM10		1 lamp EM	350 - 450								■	■			■	■									
B100LP	EM10LP		Low Profile 1 lamp EM	350 - 450													■									
LP500	EMLP5		Low Profile T5 1 lamp EM	370 - 520																	■	■				
LP550	EMLP55		Low Profile TT T5HO, T8 1 lamp EM	390 - 700									■	■	■			■			■	■	■	■	■	■
LP600	EMLP6		Low Profile TT T5, T5HO, T8 1 lamp EM	650 - 1325									■	■	■	■	■	■			■	■	■	■	■	■

DRY LOCATION	DAMP LOCATION
B50	BDL500
B60	BDL600
B70A	BDL700
B90	BDL900

GENERAL NOTES:

- When multiple lamp operation is selected, lumen output is evenly distributed between lamps.
- Emergency ballasts provide illumination for a minimum of 90 minutes.
- Standard emergency ballasts are UL listed for dry locations only. For damp locations, specify models ending in "DL".

FOOTNOTES:

1 May require back or remote mounting — consult factory.

2 Equipped with flexible conduit.

3 B94 available — same operating characteristics as B94C.

4 Provides emergency lighting for 2 hours with 17 - 32 watt T8.

DL Damp location available suitable for use in 0°C to 50°C ambient.