





INFORMATION

SUSPENDED PRODUCT ACCESSORIES

FEEDER FIXTURE - MICROSTEM & CANOPY	
	<p>MSF/18 (2) 18" Microstems (1/4" I.P.S.) & (2) canopies for feeder fixture. Necessary hardware included.</p> <p>MSF/24 (2) 24" Microstems (1/4" I.P.S.) & (2) canopies for feeder fixture. Necessary hardware included.</p>


FEEDER FIXTURE - 1/16" DIA. AIRCRAFT CABLE	
	<p>ACF__</p> <p>Available in adjustable 48" or 96" lengths. Necessary hardware included.</p>


JOINER FIXTURE - MICROSTEM & CANOPY	
	<p>MSJ/18 (1) 18" Microstem (1/4" I.P.S.) & (1) canopy for joiner fixture. Necessary hardware included.</p> <p>MSJ/24 (1) 24" Microstem (1/4" I.P.S.) & (1) canopy for joiner fixture. Necessary hardware included.</p>


JOINER FIXTURE - 1/16" DIA. AIRCRAFT CABLE	
	<p>ACJ__</p> <p>Available in adjustable 48" or 96" lengths. Necessary hardware included.</p>

NOTES:


- Electrical supply is brought into the feeder fixture, either as part of a row, or as an individual mount unit. Joiner fixtures complete the row
- Above mentioned mounting accessories are for standard NEMA type "G" T-bar ceilings
- For slot grid (NEMA type "SS"), add suffix "SG" to catalog number. Example: ACF - **SG**/48
- For hard pan ceilings, add suffix "HP" to catalog number. Example: ACF - **HP**/48


CORD FOR SUSPENDED PRODUCT	
	<p>CORD TYPE — S = Straight</p> <p>NUMBER OR CONDUCTORS — 3, 4, or 5</p> <p>S4838/W</p> <p>LENGTH IN INCHES — 48" or 96"</p> <p>WIRE SIZE — 4 = No. 14 AWG, 8 = No. 18 AWG</p> <p>COLOR — W = White, B = Black (straight cord only)</p>


90° CORNERS	
	<p>90° corners are available for AI2, AI3, AI4, AI5, WS and XT series products. To order specify AI2, AI3, AI4, AI5, WS and XT corner kit</p>

GRIPPLE® HANG-FAST SUSPENSION SYSTEM	
	<p>GC2/Y18/_</p> <p>Adjustable cable suspension system — available in lengths of 5', 10', 15', and 30'</p>

ELECTRICAL ACCESSORIES

CORD & PLUG	
	<p>6CPI/5-15P 120V, 6' cord & plug, No. 18 AWG, 3 conductor, NEMA 5 - 15 plug</p> <p>6CPI/7-15P 277V, 6' cord & plug, No. 18 AWG, 3 conductor, NEMA 7 - 15 plug</p>

BALLAST SUPPRESSOR	
	<p>SUPPRESSOR</p> <p>Ballast suppressor, for most Williams products — consult factory</p> <p>Note: Not recommended with dimming or electronic ballasts</p>

FUSE	
	<p>GLR Fast blow fuse</p> <p>GMF Slow blow fuse</p>