










CEILING COMPATIBILITY


	<p style="text-align: center;">NEMA "F" (Flange)</p> <p>NEMA Type "F" fixtures ship with the side trims, end trims, and swing-out brackets assembled to the fixture. See specification sheets for exact dimensions of swing-out bracket vertical adjustment and ceiling cut-out.</p>
---	---


	<p style="text-align: center;">NEMA "G"</p> <p>All Williams grid fixtures (NEMA Type "G") are designed to fit securely into a standard NEMA Type "G", 1" nominal T-bar system. Center the fixture in the opening and use earthquake clips or integral T-bar clips to secure the fixture to the ceiling structure.</p>	
---	--	---


	<p style="text-align: center;">NEMA STYLE "SS" SCREW SLOT GRID (WILLIAMS' SG)</p> <p>Williams' NEMA Type "SS" troffers are designed such that the bottom of the door frame of the louver is flush with the ceiling tile. Center the fixture in the opening and use earthquake clips to secure the fixture to the ceiling structure. Available on specific styles of parabolic louvers and recessed indirect only. (Earthquake clips required.)</p>	
---	---	---

<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>NEMA "NFG" Narrow Faced Grid</p> </div> <div style="text-align: center;">  <p>NEMA "NFSG" Narrow Faced Slotted Grid</p> </div> <div style="text-align: center;">  <p>NEMA "SS" Screw Slot Grid</p> </div> <div style="text-align: center;">  <p>NEMA "Z" Z Spline</p> </div> </div>	<p style="text-align: center;">SPECIALTY CEILING TEE</p> <p>Please contact the factory before ordering troffers to be fitted with specialty T-bar systems to assure proper compatibility. Dimensions and specifications are subject to change without notice.</p>
--	--

TROFFER OPTIONS

	<p style="text-align: center;">DOUBLE GASKETING</p> <p>Fixtures must be equipped with flat aluminum door frame for this option. Closed cell PVC gasketing with mylar coating is factory installed continuously between door frame and luminaire housing and between door frame and lens. Use catalog number designation "-DG" Example: EPG-S24-332-FA12125-DG-EB3-120</p>
---	--

	<p style="text-align: center;">TRIPLE GASKETING</p> <p>For series 50 and EP™ equipped with flat aluminum door frame. Closed cell PVC gasketing with mylar coating is factory installed continuously between door frame and luminaire housing, between door frame and lens, and on bottom perimeter of unit (adjacent to T-bar). NEMA type "F" units feature gasketing attached to top surface of flange trim (adjacent to ceiling surface). Use catalog number designation "-TG" Example: EPG-S24-332-FA12125-TG-EB3-120</p>
--	---

	<p style="text-align: center;">EARTHQUAKE CLIPS</p> <p>Combination earthquake and N.E.C. T-bar clip secures luminaire to T-bar and prevents T-system separation. Clips are factory installed; 4 clips per fixture. Suffix catalog number with "EQ Clips" Example: HE3G-D24-332-36S-EQCLIPS-EB3-120</p>
--	---