

VANDAL RESISTANT POST TOP


OAA

SUBMITTAL:

JOB:

TYPE:

VOLTAGE:



EXAMPLE:

OAA - 250PSMH120 - T5 - DBR - OPTIONS

SERIES

ELECTRICAL PACKAGE


PHOTO. DIST.

FINISH OPTIONS

OPTIONS

SERIES

OAA — The OAA Series is an attractive alternative for vandal-prone, high-traffic or recreational area lighting. Our one-piece cast aluminum housing is designed with 18 precisely spaced fins to prevent baseball-sized objects from making contact with the lens. The OAA's combined good looks and practical engineering provide a perfect choice for parks, sports facilities and public spaces.



Total fixture EPA: 2.56/Weight: 42 Lbs.



OAA SERIES

HOUSING — One-piece, cast aluminum lens guard and ballast compartment. Heavy-gauge spun aluminum top with underside reflector painted a highly-reflective, non-glare white powder coat.

LENS — One-piece, high-impact-resistant polycarbonate refractor available in Type II and Type V distributions.

ELECTRICAL PACKAGE (Must specify)

PULSE START METAL HALIDE

Lamp:	E17	E17	E17	BT28
Socket:	E26 Medium	E26 Medium	E26 Medium	E39 Mogul
ANSI Ballast Code:	M98	M90	M102	M153
	70PSMH120	100PSMH120	150PSMH120	250PSMH120
	70PSMH208	100PSMH208	150PSMH208	250PSMH208
	70PSMH240	100PSMH240	150PSMH240	250PSMH240
	70PSMH277	100PSMH277	150PSMH277	250PSMH277
	70PSMH347	100PSMH347	150PSMH347	250PSMH347
		100PSMH480	150PSMH480	250PSMH480

HIGH PRESSURE SODIUM

Lamp:	E17	E17	E17	ET18
Socket:	E26 Medium	E26 Medium	E26 Medium	E39 Mogul
ANSI Ballast Code:	S62	S54	S55	S50
	70HPS120	100HPS120	150HPS120	250HPS120
	70HPS208	100HPS208	150HPS208	250HPS208
	70HPS240	100HPS240	150HPS240	250HPS240
	70HPS277	100HPS277	150HPS277	250HPS277
	70HPS347	100HPS347	150HPS347	250HPS347
		100HPS480	150HPS480	250HPS480

ELECTRICAL PACKAGE

PSMH — Rated -20°F minimum starting temperature.

HPS — Rated -40°F minimum starting temperature.

All PSMH and HPS electrical packages include porcelain socket. Integral ballast. Prewired at factory for easy field installation. HX-HPF or CWA ballast type standard. Lamp is optional, please specify when ordering.

PHOTOMETRIC DISTRIBUTION (Must specify)



T2
Type II



T5
Type V



FINISH OPTIONS

Super durable polyester powder coat meets and exceeds AAMA 2604 specifications for outdoor durability.

MOUNTING

Post top mounting on 2-7/8" O.D. tenon. Secured with stainless steel set screws. See Williams' Poles or Pole Top Assemblies for details.

LABELS

cCSAus certified as luminaire suitable for wet location.

FINISH OPTIONS (Must specify)

BLK	Black (RAL# 9004)	DBR	Dark bronze (Protech #PC21462)
GRAY	Standard gray (Protech #PC18367)	GRN	Green (RAL# 6005)
SLV	Satin aluminum (RAL# 9006)	WHT	White (RAL# 9003)
RAL# _____	Specify custom color		

OPTIONS

SF	Single fuse (120V, 277V, or 347V only; must specify voltage)
DF	Double fuse (208V, 240V, or 480V only; must specify voltage)

