


# 24" ROUND YOKE MOUNT AREA LIGHT WITH HORIZONTAL LAMP

# OBSH24



**SUBMITTAL:**

**JOB:**

**TYPE:**

**VOLTAGE:**

EXAMPLE:

**OBSH24 - 400PSMH120 - T3 - DBR - OPTIONS**

SERIES

ELECTRICAL PACKAGE

DIST.

FINISH OPTIONS


OPTIONS/ ACCESSORIES



This fixture is proudly made in the USA.

## SERIES

- ▶ Yoke mount design for pole top mounting.
- ▶ Spring latches lock hinged fixture housing into place for easy relamping.
- ▶ Architecturally designed with a horizontal reveal.
- ▶ HID lamping up to 400 watts.
- ▶ 90° rotatable reflector allows orientation to be easily altered on-site.
- ▶ Highly specular, multi-faceted aluminum reflector.
- ▶ Optional reflector-mounted house shield available.



EPA: 1.94/Weight: 47 Lbs.

## OBSH24 SERIES

**HOUSING** — One-piece spun aluminum housing, .100" wall thickness, with internal reinforcement and component bracketing.

**DOOR** — Cast aluminum hinged door fastened using stainless steel hardware.

**LENS** — Clear, .187" thick high-impact, heat-resistant tempered glass flat lens, secured with retaining clips, sealed with silicone.

## ELECTRICAL PACKAGE (Must specify)

### PULSE START METAL HALIDE

Lamp:	E17	BT28	BT28	BT37
Socket:	E26 Medium	E39 Mogul	E39 Mogul	E39 Mogul
ANSI Ballast Code:	M102	M153	M154	M155
	150PSMH120	250PSMH120	320PSMH120	400PSMH120
	150PSMH208	250PSMH208	320PSMH208	400PSMH208
	150PSMH240	250PSMH240	320PSMH240	400PSMH240
	150PSMH277	250PSMH277	320PSMH277	400PSMH277
	150PSMH347	250PSMH347	320PSMH347	400PSMH347
	150PSMH480	250PSMH480	320PSMH480	400PSMH480

### HIGH PRESSURE SODIUM

Lamp:	E17	ET18	ET18
Socket:	E26 Medium	E39 Mogul	E39 Mogul
ANSI Ballast Code:	S55	S50	S51
	150HPS120	250HPS120	400HPS120
	150HPS208	250HPS208	400HPS208
	150HPS240	250HPS240	400HPS240
	150HPS277	250HPS277	400HPS277
	150HPS347	250HPS347	400HPS347
	150HPS480	250HPS480	400HPS480

## ELECTRICAL PACKAGE

**PSMH** — Rated -20°F minimum starting temperature.

**HPS** — Rated -40°F minimum starting temperature.

All PSMH and HPS electrical packages include porcelain socket. Core and coil ballast mounted on removable ballast tray. Prewired at factory to a disconnect plug for easy field installation. HX-HPF or CWA ballast type standard. Lamp is optional, please specify when ordering.



# OBSH24

## 24" ROUND YOKE MOUNT AREA LIGHT WITH HORIZONTAL LAMP

### REFLECTOR

Precisely formed highly specular, multi-faceted aluminum reflector secured with thumb screws. The reflector can be rotated in 90° increments allowing orientation to be altered on-site.

### FINISH OPTIONS

Super durable polyester powder coat meets and exceeds AAMA 2604 specifications for outdoor durability.

### MOUNTING

Yoke mount consists of two parallel 1" O.D. aluminum tubes formed and welded to a cast aluminum door and slip fitter. Fits 3" O.D. x 3" tenon or pole top.

### LABELS

cCSAus certified as luminaire suitable for wet locations.

### DISTRIBUTION (Must specify)



**T2**  
Type II



**T3**  
Type III



**TFT**  
Type forward throw



**T5**  
Type V


### FINISH OPTIONS (Must specify)

<b>BLK</b>	Black (RAL #9004)
<b>DBR</b>	Dark bronze (Protech #PC21462)
<b>GRAY</b>	Standard gray (Protech #PC18367)
<b>GRN</b>	Green (RAL #6005)
<b>SLV</b>	Satin aluminum (RAL #9006)
<b>WHT</b>	White (RAL #9003)
<b>RAL#</b> _____	Specify custom color

### OPTIONS


<b>SF</b>	Single fuse (120V, 277V, or 347V only; must specify voltage)	<b>DF</b>	Double fuse (208V, 240V, or 480V only; must specify voltage)
-----------	--	-----------	--

### ACCESSORIES



**DHS** Reflector-mounted house shield

### RELAMPING FEATURE



Spring latches lock hinged fixture housing into place for easy relamping. For detailed relamping instructions go to [www.hewilliams.com](http://www.hewilliams.com).

