

# 10" ROUND CONCRETE BOLLARD

# OSC10R

**SUBMITTAL:**

**JOB:**

**TYPE:**

**VOLTAGE:**



**CFL**

**EXAMPLE:** **OSC10R - 42TUNV - VG - FT - NC - DBR - AB - OPTIONS**

SERIES

ELECTRICAL PACKAGE

SHIELD

HOUSING TOP

HOUSING COLOR


SHIELD FINISH

ANCHOR BOLTS


OPTIONS

## SERIES


This fixture is proudly made in the USA.




Dome Top (DT) / Vertical Cast Grill (VG)  
Weight: 188 Lbs.




Dome Top (DT) / Horizontal Cast Grill (HG)  
Weight: 194 Lbs.




Dome Top (DT) / Louvered Cast Grill (LG)  
Weight: 191 Lbs.



Flat Top (FT) / Vertical Cast Grill (VG)  
Weight: 194 Lbs.



Flat Top (FT) / Horizontal Cast Grill (HG)  
Weight: 200 Lbs.




Flat Top (FT) / Louvered Cast Grill (LG)  
Weight: 197 Lbs.


## ELECTRICAL PACKAGE (Must specify)

|         |        |        |         |         |         |
|---------|--------|--------|---------|---------|---------|
| Socket: | G24q-2 | G24q-3 | GX24q-3 | GX24q-3 | GX24q-4 |
|         | 18Q120 | 26Q120 | 26T120  | 32T120  | 42T120  |
|         | 18Q208 | 26Q208 | 26T208  | 32T208  | 42T208  |
|         | 18Q240 | 26Q240 | 26T240  | 32T240  | 42T240  |
|         | 18Q277 | 26Q277 | 26T277  | 32T277  | 42T277  |
|         | 18QUNV | 26QUNV | 26TUNV  | 32TUNV  | 42TUNV  |
|         | 18Q347 | 26Q347 | 26T347  | 32T347  | 42T347  |


## SHIELD (Must specify)



**VG** Vertical cast grill with opal diffuser



**HG** Horizontal cast grill with opal diffuser



**LG** Louvered cast grill with clear diffuser

## OSC10R SERIES HOUSING —

Prestressed, reinforced, cast hollow core concrete with a light sand blasted finish. Concrete top and cast aluminum shield are removable as one unit to provide access to lamp and ballast.

## ELECTRICAL PACKAGE

Rated 0°F minimum starting temperature. Prewired at factory for easy field installation. Ballast mounted on removable tray for ease of maintenance. Lamp is optional, please specify when ordering.

## SHIELD

Cast aluminum grill is .188" thick with an opal (HG or VG) or clear (LG) U.V. stabilized acrylic diffuser. Shield is secured to housing with stainless steel tamper-proof hardware.

## CFL

### HOUSING TOP

Cast, prestressed, reinforced concrete.

#### HOUSING TOP (Must specify)

|                    |                    |
|--------------------|--------------------|
| <b>DT</b> Dome top | <b>FT</b> Flat top |
|--------------------|--------------------|

#### HOUSING COLOR/FINISH (Must specify)

|  |  |
|--|--|
| <b>NC</b> Natural concrete color/finish (Standard) | <b>CC</b> _____ Specify custom concrete color/finish (Consult factory) |
|--|--|

### SHIELD FINISH

Super durable polyester powder coat meets and exceeds AAMA 2604 specifications for outdoor durability.

#### SHIELD FINISH (Must specify)

|  |   |
|--|---|
| <b>BLK</b> Black (RAL #9004)                 | <b>DBR</b> Dark bronze (Protech #PC21462) |
| <b>GRAY</b> Standard gray (Protech #PC18367) | <b>GRN</b> Green (RAL #6005)              |
| <b>SLV</b> Satin aluminum (RAL #9006)        | <b>WHT</b> White (RAL #9003)              |
| <b>RAL#</b> _____ Specify custom color       |   |

#### ANCHOR BOLTS (Must specify)

|   |                              |
|---|------------------------------|
| <b>AB</b> <sup>1</sup> Anchor bolts (4 each, shipped with fixture) <sup>1</sup> | <b>LAB</b> Less anchor bolts |
| <b>PAB</b> <sup>1</sup> Pre-shipped anchor bolts (4 each) <sup>1</sup>          |                              |

<sup>1</sup> Four 3/8" x 12" cast-in galvanized steel anchor J-bolts. Mounting template included.


#### OPTIONS

|  |   |
|--|---|
| <b>SF</b> Single fuse (120V, 277V, or 347V only; must specify voltage) | <b>DF</b> Double fuse (208V or 240V only; must specify voltage) |
|--|---|

### MOUNTING

4-Point, hot dip galvanized carbon steel base. For accurate installation a full-scale mounting template is provided with every bollard and anchor bolt order.


#### TEMPLATE



Mounting template (Provided with each order)

A pdf file (not to-scale) of the mounting template is available online at [www.hewilliams.com](http://www.hewilliams.com).

#### DISTRIBUTION



T5 Type V

### LABELS



cETLus conforms to UL STD 1598; Certified to CAN/CSA STD C22.2 No. 250.0. Suitable for wet locations.