

# VINTAGE PRISMATIC ACORN POST TOP

# OPC


## INDUCTION

**SUBMITTAL:**

**JOB:**

**TYPE:**

**VOLTAGE:**



**EXAMPLE:** **OPC** - **85QL120** - **40K** - **ACR** - **T5** - **4TM** - **DBR** - **OPTIONS**

SERIES

ELECTRICAL PACKAGE

COLOR TEMP.

DIFFUSER

DISTRIBUTION

MOUNTING POINT

FINISH OPTIONS


OPTIONS



### SERIES

#### FEATURES

- ▶ 100,000 hour lamp life significantly reduces maintenance where relamping is inconvenient or expensive.
- ▶ Induction lamps provide excellent lumen maintenance—70% at 60,000 hours.
- ▶ 80 color rendering index (CRI).
- ▶ -25°C/-13°F minimum operating ambient temperature, 40°C/104°F maximum operating ambient temperature.
- ▶ Choice of clear, textured U.V. stabilized acrylic or impact-resistant polycarbonate diffuser.
- ▶ Prismatic band provides optimal Type III or Type V distribution.
- ▶ Optional brass finial available.



Total fixture EPA: 1.40/Weight: 28 Lbs.

#### OPC SERIES HOUSING —

Cast aluminum base with clear, textured U.V. stabilized acrylic or impact-resistant polycarbonate diffuser. Gasketed for weathertight performance.

#### ELECTRICAL PACKAGE (Must specify)

##### QL INDUCTION SYSTEM

55QL120	85QL120
55QL208	85QL208
55QL240	85QL240
55QL277	85QL277

#### ELECTRICAL PACKAGE

3-piece Philips QL Induction system. Prewired at factory for easy field installation.

#### LAMP COLOR TEMPERATURE (Must specify)

<b>27K</b>	2700K
<b>30K</b>	3000K
<b>40K</b>	4000K

#### DIFFUSER (Must specify)

<b>ACR</b>	Acrylic diffuser	<b>CPC</b>	Polycarbonate diffuser
------------	------------------	------------	------------------------

#### DIFFUSER

Molded U.V. stabilized acrylic or molded impact-resistant polycarbonate.

## INDUCTION

### DISTRIBUTION

Integral prismatic band provides Type III or Type V distribution.

### DISTRIBUTION (Must specify)



**T3** Type III



**T5** Type V

### MOUNTING POINT

Post top mounting on 3" or 4" O.D. tenon or pole top. Secured with stainless steel set screws. See Williams' Poles or Pole Top Assemblies for details.

### MOUNTING POINT (Must specify)

**3TM** 3" tenon mount

**4TM** 4" tenon mount

### FINISH OPTIONS

Super durable polyester powder coat meets and exceeds AAMA 2604 specifications for outdoor durability.

### FINISH OPTIONS (Must specify)

**BLK** Black (RAL #9004)

**DBR** Dark bronze (Protech #PC21462)

**GRAY** Standard gray (Protech #PC18367)

**GRN** Green (RAL #6005)

**SLV** Satin aluminum (RAL #9006)

**WHT** White (RAL #9003)

**RAL#\_\_\_\_\_** Specify custom color

### OPTIONS

**SF** Single fuse (120V or 277V only; must specify voltage)

**DF** Double fuse (208V or 240V only; must specify voltage)



**FIN** Solid brass finial

### LABELS

cCSAus certified as luminaire suitable for wet location.

