

VINTAGE ACORN POST TOP

OPD


INDUCTION

SUBMITTAL:

JOB:

TYPE:

VOLTAGE:



EXAMPLE: **OPD - 85QL120 - 40K - ACR - T5BL - 4TM - DBR - OPTIONS**

SERIES

ELECTRICAL PACKAGE

COLOR TEMP.

DIFFUSER

DISTRIBUTION

MOUNTING POINT

FINISH OPTIONS


OPTIONS



SERIES

FEATURES

- ▶ 100,000 hour lamp life significantly reduces maintenance where relamping is inconvenient or expensive.
- ▶ Induction lamps provide excellent lumen maintenance—70% at 60,000 hours.
- ▶ 80 color rendering index (CRI).
- ▶ -25°C/-13°F minimum operating ambient temperature, 40°C/104°F maximum operating ambient temperature.
- ▶ Choice of clear, textured U.V. stabilized acrylic or impact-resistant polycarbonate diffuser.
- ▶ Brass bullet-style finial option for a decorative touch.



Total fixture EPA: 1.22/Weight: 27 Lbs.

OPD SERIES HOUSING —

Cast aluminum base with clear, textured U.V. stabilized acrylic or impact-resistant polycarbonate diffuser. Gasketed for weathertight performance.

ELECTRICAL PACKAGE (Must specify)

QL INDUCTION SYSTEM

55QL120	85QL120
55QL208	85QL208
55QL240	85QL240
55QL277	85QL277

ELECTRICAL PACKAGE

3-piece Philips QL Induction system. Prewired at factory for easy field installation.

LAMP COLOR TEMPERATURE (Must specify)

27K	2700K
30K	3000K
40K	4000K

DIFFUSER

Molded U.V. stabilized acrylic or molded impact-resistant polycarbonate.

DIFFUSER (Must specify)

ACR	Acrylic diffuser	CPC	Polycarbonate diffuser
------------	------------------	------------	------------------------

DISTRIBUTION



T5BL Type V bare lamp

DISTRIBUTION

Type V distribution.

MOUNTING POINT (Must specify)

3TM	3" tenon mount
4TM	4" tenon mount

MOUNTING POINT

Post top mounting on 3" or 4" O.D. tenon or pole top. Secured with stainless steel set screws. See Williams' Poles or Pole Top Assemblies for details.



INDUCTION

FINISH OPTIONS

Super durable polyester powder coat meets and exceeds AAMA 2604 specifications for outdoor durability.

FINISH OPTIONS (Must specify)

BLK	Black (RAL #9004)
DBR	Dark bronze (Protech #PC21462)
GRAY	Standard gray (Protech #PC18367)
GRN	Green (RAL #6005)
SLV	Satin aluminum (RAL #9006)
WHT	White (RAL #9003)
RAL# _____	Specify custom color

OPTIONS

SF	Single fuse (120V or 277V only; must specify voltage)	DF	Double fuse (208V or 240V only; must specify voltage)
-----------	---	-----------	---



FIB	Solid brass bullet-style finial
------------	---------------------------------

LABELS

cCSAus certified as luminaire suitable for wet location.