

# GLOBE LUMINAIRE

# OGO


**SUBMITTAL:**

**INDUCTION**

**JOB:**

**TYPE:**

**VOLTAGE:**



**EXAMPLE:** **OGO 18 - 85QL120 - 40K - ACR - WHT - T5BL - DBR**


SERIES    GLOBE SIZE    ELECTRICAL PACKAGE    COLOR TEMP.    GLOBE MATERIAL    GLOBE COLOR    DIST.    FINISH OPTIONS

## SERIES

### FEATURES

- ▶ 100,000 hour lamp life significantly reduces maintenance where relamping is inconvenient or expensive.
- ▶ Induction lamps provide excellent lumen maintenance—70% at 60,000 hours.
- ▶ 80 color rendering index (CRI).
- ▶ -25°C/-13°F minimum operating ambient temperature, 40°C/104°F maximum operating ambient temperature.
- ▶ Choice of impact-resistant polycarbonate or U.V. stabilized acrylic diffuser.
- ▶ Choice of clear or white globe.

This fixture is proudly made in the USA.



## OGO SERIES

Available in 16", 18", 20", or 22" globe sizes.

**FIXTURE BASE** — Cast aluminum base with integral slip fitter and spun aluminum cover.

**ENCLOSURE** — Impact-resistant polycarbonate (16", 18", and 20" only) or U.V. stabilized acrylic globe. Gasketed for weathertight performance.

## GLOBE SIZE (Must specify)

GLOBE SIZE	A	B	EPA	WEIGHT
16	ø16"	16-1/2"	0.86	20 Lbs.
18	ø18"	18-5/8"	1.09	21 Lbs.
20	ø20"	20-11/16"	1.33	21 Lbs.
22	ø22"	22-13/16"	1.61	23 Lbs.

## ELECTRICAL PACKAGE (Must specify)

### QL INDUCTION SYSTEM

55QL120	85QL120
55QL208	85QL208
55QL240	85QL240
55QL277	85QL277

## ELECTRICAL PACKAGE

3-piece Philips QL Induction system. Prewired at factory for easy field installation.

## LAMP COLOR TEMPERATURE (Must specify)

27K	2700K
30K	3000K
40K	4000K

## GLOBE MATERIAL

Impact-resistant polycarbonate (16", 18", and 20" only) or U.V. stabilized acrylic.

## GLOBE MATERIAL (Must specify)

ACR	Acrylic
CPC	Polycarbonate (16", 18", 20" only)

## GLOBE COLOR (Must specify)

CLR	Clear
WHT	White

## GLOBE COLOR

Available in clear or white.

## INDUCTION

## DISTRIBUTION

### DISTRIBUTION

Type V distribution.



**T5BL** Type V bare lamp

### FINISH OPTIONS

Super durable polyester powder coat meets and exceeds AAMA 2604 specifications for outdoor durability.

### FINISH OPTIONS (Must specify)

<b>BLK</b>	Black (RAL# 9004)
<b>DBR</b>	Dark bronze (Protech #PC21462)
<b>GRAY</b>	Standard gray (Protech #PC18367)
<b>GRN</b>	Green (RAL# 6005)
<b>SLV</b>	Satin aluminum (RAL# 9006)
<b>WHT</b>	White (RAL# 9003)
<b>RAL#</b> ____	Specify custom color

### MOUNTING POINT

Integral slip fitter mounts on 3" O.D. tenon or pole top. Secured with stainless steel set screws. See Williams' Poles or Pole Top Assemblies for details.

### LABELS

cCSAus certified as luminaire suitable for wet location.

