



STRIPS / INDUSTRIALS / WRAPS MOUNTING



MYERS SWAY ADAPTER	
MSA-1	Myers Sway Adapter for use with any 3/8" I.P.S. stem



SINGLE STEM & CANOPY – SS			
SS-8	8" stem and canopy	SS-24	24" stem and canopy
SS-12	12" stem and canopy	SS-36	36" stem and canopy
SS-18	18" stem and canopy		

CANOPY: Die formed 24 GA. C.R.S. 5" diameter x 1 7/16" deep fully covering outlet box. Equipped with 5/8" canopy slip ring and screw.


CEILING MOUNTING BRACKET: Durable, die formed, 12 GA. C.R.S. Can be mounted to tee bar with assistance of a tee bar clamp or directly to ceiling. (Tee Bar Clamp not furnished.)

STEM: 3/8" IPS (5/8" O.D.) steel tubing- (specify length)

NUTS: Heavy duty 3/8" square, corner notched lock nuts.

FINISH: Durable long lasting baked white enamel.

MOUNTING BRACKET



STEM & SWIVEL CANOPY – SWS			
SWS-8	8" stem and swivel canopy	SWS-24	24" stem and swivel canopy
SWS-12	12" stem and swivel canopy		

CANOPY: Die formed 20 GA. C.R.S. 5" diameter x 1 5/8" deep fully covering outlet box.

CEILING MOUNTING BRACKET: Durable, die formed, 16 GA. C.R.S. Can be mounted to outlet box or flat surface.


SWIVEL NUT: Cast metal swivel nut. Allows stem to adjust up to 40 degree alignment.

STEM: 3/8" IPS (5/8" O.D.) steel tubing- (specify length)

NUTS: Heavy duty 3/8" square, corner notched lock nuts.

FINISH: Durable long lasting baked white enamel.

MOUNTING BRACKET



STEM & DOUBLE CANOPY – DS			
DS-12	12" stem and double canopy	DS-24	24" stem and double canopy

DOUBLE CANOPY: Die formed 24 GA. C.R.S. 5" wide x 12" long x 1 3/4" deep fully covers outlet box. Equipped with (2) 5/8" canopy slip rings and screws

CEILING MOUNTING BRACKET: Durable, die formed, 18 GA. C.R.S. Can be mounted to outlet box or flat surface.

STEM: 3/8" IPS (5/8" O.D.) steel tubing- (specify length)

NUTS: Heavy duty 3/8" square, corner notched lock nuts.

FINISH: Durable long lasting baked white enamel.

MOUNTING BRACKET




H. E. WILLIAMS, INC.

H.E. Williams, Inc. • Carthage, Missouri • www.hewilliams.com • 417-358-4065 • Fax: 417-358-6015


Information page 2

Information contained herein is subject to change without notice.


STRIPS / INDUSTRIALS / WRAPS MOUNTING



T2 TONG HANGER	
T2	Tong type hanger for use with 77, 78, 81, 82, 83, & 85



320 & 325 CEILING SPACERS	
320	1 1/2" ceiling spacer for use with 76 & 80
325	1 1/2" ceiling spacer for use with 77, 78, 81, 82, 83, & 85




GAT FASTENER	
GAT	T-bar attachment for 320 & 325 ceiling spacer. For use with strips, industrials, wraps, & surface mounts




VBY HANGER	
VBY	"Y" hanger (2). For use with 76, 77, 78, 80, 81, 82, 83, & 85
VBY-2	"Y" hanger w/2' chain (2). For use with 76, 77, 78, 80, 81, 82, 83, & 85
VBY-3	"Y" hanger w/3' chain (2). For use with 76, 77, 78, 80, 81, 82, 83, & 85


STRIPS / INDUSTRIALS




ML-4 - ML-5	
ML-4	48" metal louver. For use with 82 & 83 with SL, HO, and VHO lamps
ML-5	50" metal louver. For use with 82 & 83 with T8, T12 medium Bi-pin lamps



M4-A12125 - M5-A12125	
M4-A12125	48" metal frame with #12 pattern lens. For use with 82 & 83 with SL, HO, and VHO lamps
M5-A12125	50" metal frame with #12 pattern lens. For use with 82 & 83 with T8, T12 medium Bi-pin lamps




EP 82	
EP 82	Reflector end plates. For use with 82, 83, & 85



RA 80	
RA 80	Reflector row aligner. For use with 80, 82, 83, & 85



RA 82	
RA 82	Reflector row aligner—specification grade. For use with 82, 83, & 85



WIRE GUARD—WHEN ORDERED AS SEPARATE LINE ITEM	
WG = Wire guard	11 = 11 Ga. white powder coat 14 = 14 Ga. white powder coat
WG7611-4	
73 = Series 73 76 = Series 76 75 = Series 5 80 = Series 80 or 81 82 = Series 82, or, or 85 Standard finish is white powder coat. For Zinc finish, suffix catalog number with "Zinc"	Nominal Length 2 = 2 ft. 3 = 3ft. 4 = 4 ft.